


Side Weld Seals 3/8 in (+/- 1/8")

^{**} Bags are printed (hot stamped or thermal transferred) with an ESD protective symbol and a lot code for traceability.





Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7057.



STATFREE® ESD ULTRA CLEAR BAG



Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and Static Control Bag standard ANSI/ESD S11.4 Level 5.

Specifications:

Electrical Properties	Typical Value	Test Procedures/Method
Surface Resisitance:		
(Interior and Exterior)	$1 \times 10^4 \text{ to} < 1 \times 10^{11} \text{ ohms}$	per ANSI/ESD STM11.11
Charge Generation:		
Teflon	-0.10 (nC/in ²) +0.10 (nC/in ²)	Modified Incline Plane
Quartz	+0.10 (nC/in ²)	Modified Incline Plane

Physical Properties:

J		
Thickness	Nominal 3.5mil (.09mm) ±10%	MIL-STD-3010, 1003
Width (Inside Dimensions)	Nominal -0" / + 1/4"	
Length (Inside Dimensions)	Nominal +/- 1/8", Offset 0" to 1/4"	
Light Transmission	>90 (%)	STM D-1003
Heat Seal	>8 (lbs/in)	375°F, .75 sec 60 psi
Tensile Strength	>5,300 (MD/TD, psi)	ASTM D-882
Puncture Resistance	>14 lbs	MIL-STD-3010, 2065
Silicone	Not detected	FTIR
MVTR	0.35 (grams / 100 in² / 24 hrs)	ASTM F-1249

Chemical Properties

Polycarbonate compatible: Contains no Amines, Amides, or N-Octanoic Acid.

Bag is free of amines, N-octanoic acid, silicones and heavy metals.

ANSI/ESD S541 section 6.1 Inside an EPA

"Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

- Low charge generation
- · Dissipative or conductive materials for intimate contact"

RoHS, REACH and Conflict Minerals, Statement

See the Desco Industries RoHS, REACH, and Conflict Minerals Statement:

https://desco.descoindustries.com/pdf/Regulatory Statements Desco Statshield Bags.pdf

See the Desco Limited Warranty:

Desco.DescoIndustries.com/Limited-Warranty.aspx

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.



Specifications and procedures subject to change without notice.

STATFREE® ESD ULTRA CLEAR BAG WITH ZIPPER, 3.5MIL (.09mm)

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407

PHONE (781) 821-8370

DRAWING NUMBER 13880

DATE: September 2021