

Band Size	Circumference	
	Min.	Max.
Small	5.5" (140mm)	9" (229mm)
Medium	6" (152mm)	11" (279mm)
Large	7" (178mm)	12" (305mm)

Item	Band Size	Coil Cord
<u>19886</u>	Small	Not Included
<u>19887</u>	Medium	Not Included
<u>19888</u>	Large	Not Included
<u>19900</u>	Small	6' ( <u>19906</u> )
<u>19901</u>	Medium	6' ( <u>19906</u> )
<u>19902</u>	Large	6' ( <u>19906</u> )
<u>19903</u>	Small	12' ( <u>19907</u> )
<u>19904</u>	Medium	12' ( <u>19907</u> )
<u>19905</u>	Large	12' ( <u>19907</u> )

- A. .002" polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a <u>Desco MagSnap™ 360 Coil Cord</u> (not included) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.63".
- Black ABS plastic insulator separates band into halves.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

All tolererances are 10% unless otherwise specified. Specifications and procedures are subject to change without notice.





U.S. Patent Pending

MAGSNAP 360™ DUAL-WIRE METAL EXPANSION WRISTBAND



**DRAWING** NUMBER 19886

DATE February 2019