


# Anti-Fatigue Matting



Light Grey, Brown

## Description:

Statfree S™ material is specifically designed to reduce fatigue in areas where standing is required for long periods of time. This floor mat combines ESD protection and durability. The heavy embossed texture provides slip and soil resistance. Statfree S™ meets the requirements of DOD-HDBK-263, DOD-STD-2000, ESD-S7.1 and EN 100 015 Issue 1.

### RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at Desco.com.

## Electrical Properties:

Property	Test Method	Value
RTG Resistance:	ESD S7.1	10E9 - 10E10 Ohms
RTT Resistance:	ESD S7.1	10E9 - 10E10 Ohms

Electrical Properties obtained by testing to industrial standards by an independent testing laboratory @ 100 Volts and 50% relative humidity unless otherwise specified. Complete text of the test report is available upon request.

### Disclaimer:

All statements, technical data, and recommendations contained herein are based upon tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. The proper and correct applications of products and data is the responsibility of the user. Statements or recommendations not contained herein shall have no force or effect unless embodied in a written agreement signed by authorized officers of Desco Industries, Inc.

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Always trim with a sharp knife or razor blade.

## Roll Stock Item Numbers

COLOR	ITEM NO.	APPROX. WT.
BROWN STIPPLE	82063	130 lb.
LIGHT GREY STIPPLE	82064	130 lb.

### Roll Stock Size 3' x 60'

(Roll Stock beveled on sides only)

### Hardware is not included with rolls.

#### Grounding Intervals for ESD Mats

Sufficient ground cords should be used to reliably meet ANSI/ESD S20.20 Table 1 less than 1 x 10E9 ohms for work surfaces. An industry recommendation has been that continuous runs of ESD matting should be grounded at ten-foot intervals to allow proper charge decay rates with each individual ESD mat should be grounded with ground snap located no further than five feet from either end.

## Specifications:

Construction:	Foamed Homogeneous Vinyl electrical properties consistent throughout. Designed specifically to reduce fatigue as a standing surface.
Thickness:	0.375 inches (9.5mm)
Texture:	Non-directional, heavy embossed, soil and abrasion resistant
Color:	Light grey, brown
Weight:	0.65 lbs/ft <sup>2</sup> (0.317g/cm <sup>2</sup> )
Hardness:	ASTM-D-2240-75 65 Shore "00"
Wear Resistance:	Negligible-Tabor Abrader, 500 Cycles CS-17 wheels, 10,000 grams load
Heat Resistance:	-20°F to 140°F continuous

\*Color and texture may vary between lots and mills

**Grounding:** This material must be properly grounded for optimum electrical performance. Ask for Technical Bulletin TB-2000 for mat grounding instructions.

**Cleaning:** For optimum electrical performance, surface must be cleaned regularly using an ESD mat cleaner. We suggest using our Rezlore™ Surface & Mat Cleaner Item #10435 or Static-Wipes Item #10600. Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.



**Tolerances:**  
Width ± .250"  
Length ± .250" every 1 linear foot of running material.



**Limited Lifetime Warranty**  
Desco warrants for one year that Statfree® matting products will be free of defects in materials and workmanship and will guarantee dissipative/ conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by Desco Limited Warranty.



**STATFREE S™ FLOOR MAT, VINYL, HOMOGENEOUS, ANTIFATIGUE, .375" (9.5mm)**

**DESCO**

DESCO WEST: 3551 WALNUT AVE., CHINO, CA 91710 WEB SITE: www.desco.com  
PHONE (909) 627-8178 FAX (909) 627-7449  
DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407  
PHONE (781) 821-8370 FAX (781) 575-0172

MATERIAL STATFREE S™  
DRAWING PM-71

DATE:  
2/06