

# TP6/PR-F/3

CUTTING BENDING  
FORMING MACHINE FOR  
AXIAL COMPONENTS



---

43.OL03 EXTRA REINFORCED

---



The model TP6/PR-F/3 is designed for cutting and forming axial taped components. Version 43.OL03 is suitable for lead  $\varnothing$  1 to 1,3mm(.039 to .051"). Die assemblies designed for each one of the version, need to be ordered separately depending on the form required. It is possible to order special forms, supplying Olamef with drawings and specifications. This high quality machine is designed and manufactured to last long time. Preforming operations are realized in order not to mark, scratch or deform leads. It can be motorised. Waste tape ejector TNS is always already included with the machine's price..



---

PRODUCTION/HOUR  
TAPED: 7000  
LOOSE: 5000


---



TNS - 21.0013 WASTE TAPE EJECTOR IS  
ALWAYS ALREADY INCLUDED WITH THE MACHINE

# TP6/PR-F/3 STANDARD DIE ASSEMBLIES

## 430700 - STAND OFF 3MM




	MM		IN	
	min	max	min	max
<b>P</b>	12.7	60.96	.5	2.4
<b>L</b>		50		1.968
<b>c</b>	2.5		.098	
<b>h</b>	11	16	.433	.629
<b>B</b>	13	18	.511	.708
<b>d</b>	1	1.3	.039	.051
<b>D</b>	1	8	.039	.314
<b>z</b>	2	4	.078	.157

## 430900 - REDUCED PITCH



	MM		IN	
	min	max	min	max
<b>P</b>	10.16	58.42	.4	2.3
<b>L</b>		50		1.968
<b>c</b>	2.5		.098	
<b>h</b>	9	16	.354	.629
<b>B</b>	11	18	.433	.708
<b>d</b>	1	1.3	.039	.051
<b>D</b>	1	8	.039	.314
<b>z</b>	2	4	.078	.157
<b>E</b>	1.27		.05	

## 420650 - "U" BENDING



	MM		IN	
	min	max	min	max
<b>P</b>	12.7	60.96	.5	2.4
<b>L</b>		50		1.968
<b>c</b>	2.5		.098	
<b>B</b>	13	18	.511	.708
<b>d</b>	1	1.3	.039	.051
<b>D</b>	1	8	.039	.314